



Rotary Tiller

The ideal attachment for ground preparation prior to turfing, planting, seeding.

Replaceable Dual rotation and bi-directional tynes allow for effective cultivation of up to 150mm depth.

Unit has two position off-set mount for easier tilling close to obstacles

Features:

- Front edge is designed to level out uneven ground
- Exclusive two position offset mount that covers wheel tracks and allows tight cut next to obstacles
- Standard dual rotation with bi-directional tines
- Replaceable abrasion resistant knife edge allows clean edging next to sod
- Optional Scarifier assembly significantly increases productivity by combining the tractive effort and force of the loader with hydraulic horse power of the Tiller
- 2 year limited warranty

Ideal Use:

Preparing ground for turf, planting or seeding

Machine Suitability:

Skid steer loaders



Specification:	
Weight:	453Kg
Length (O.A.L)	1220mm
Height (overall)	889mm
Width (overall)	1930mm
Tilling depth (Vary time)	100-150mm
Number of Tines	32
Number of Scarifier teeth (Optional)	5
Rec Fow Range - STD	52 - 64 lpm
Optional Motor Upgrade	68 - 105 lpm
Max Pressure	240 lpm

DIGGA Head Office

Brisbane QLD

4 Octal Street,
Yatala QLD 4207
Ph: (07) 3807 3330
Fax: (07) 3807 1499

DIGGA NSW

1 Gallipoli St, Smeaton
Grange, NSW, 2567
Ph: (02) 4647 1400
Fax: (02) 4647 1433

DIGGA VIC

21 - 25 Villas Road
Dandenong VIC, 3175
Ph: (03) 9706 6171
Fax: (03) 9706 6164

DIGGA WEST

13 Yampi Way,
Willetton, WA, 6155
Ph: (08) 9457 1544
Fax: (08) 9457 0748